

Reliable Mimaki Genuine Heat-Transfer Pigment Ink PHT50*

Eco cartridge ink with aluminum pack

By adopting an aluminum-pack ink delivery system and a degassed ink design, ink jetting issues are reduced, enabling stable and consistent output.




ECO PASSPORT Certified

All colors are ECO PASSPORT certified—required for OEKO-TEX®, the international safety standard for textile products—reducing environmental impact and supporting a safer working environment.

Raster Link 7

Combining ease of use with advanced functionality

Variable printing for personalized items



Mimaki Cloud Technology PICT


PICT automatically collects operating status, ink usage, and error information, enabling accurate remote monitoring of printers and supporting more efficient business operations.

Specifications

Item		TxF330-800
Print head		On-demand piezo head (2 staggered layout)
Printing resolution		X: 600, 1200 dpi Y: 600, 900, 1,200 dpi
Ink	Type / Color	Heat transfer pigment ink PHT50 (C, M, Y, K, SB, PP, W)
	Capacity	Color: 600 ml, White: 500 ml Aluminum pack
Circulatory function		Only white
Maximum print width		800 mm (31.5 in)
Media	Maximum width	810 mm (31.9 in)
	Outer dia	Φ250 mm (9.8 in) or less
	Roll weight	45 kg (99.2 lb) or less
	Core dia	2 in / 3 in
Interface		Ethernet 1000 BASE-T, USB2.0 Hi-speed
Power		Single-phase AC100-120 V / 200-240 V±10 %, 50/60 Hz±1 Hz
Power consumption		AC 100-120 V: 800 W or less, AC 200-240 V: 1.1kW or less
Certifications		VCCI class A, FCC class A, ETL IEC 62368-1, CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH, Energy Star, RCM, KC
Dimensions (W x D x H)		2,084 mm x 700 mm x 1,389 mm (82.0 x 27.6 x 54.7 in)
Weight		161 kg (354.9 lb)

Special color plate generation

The [Fill in Contour] function—ideal for DTF printing—converts vector objects and CMYK 0% areas into a special color plate. EPS, PS, and PDF formats are supported.



Operate machines remotely

MRA

(Mimaki Remote Access)

List ink type, heater temperature, and notification alerts on a smartphone or Windows-based PC. The machine can be operated remotely with the same feeling as the control panel of the actual machine.

Ink specifications • Ink array

Item	Color	Item Code
Heat Transfer Pigment Ink PHT50 Aluminum Pack	Magenta	PHT50-C-60
	Yellow	PHT50-M-60
	Yellow	PHT50-Y-60
	Black	PHT50-K-60
ECO PASSPORT Certified ink	Sky Blue	PHT50-SB-60
	Pale Pink	PHT50-PP-60
	White	PHT50-W-50

Please prepare all necessary ink packs when setting up the ink color set.

Ink Color Set

4-Color+W



6-Color+W



Precautions
Mimaki provides the printer, ink, and RIP software. Customers are advised to conduct thorough prior evaluations when considering the film, powder, shaker (post-processing machine), and heat press transfer machine required for the DTF printing process.

Some examples shown in this catalog are artificial renderings. Specifications, designs and dimensions shown in this catalog may be subject to change without notice for technical improvements. The corporate and merchandise names in this catalog are the trademarks or registered trademarks of the respective corporations. Inkjet printers use extremely fine dots, so colors may vary slightly after replacement of print heads. Also note that when using multiple printer units, colors could vary slightly from one unit to another due to slight individual differences. Please note that descriptions and data in this catalog are as of September 2026.

Mimaki MIMAKI ENGINEERING CO., LTD.
2182-3 Shigeno-Otsu, Tomi-city, Nagano 389-0512, Japan
TEL: +81-268-64-2281

Mimaki Global Network

USA	MIMAKI USA, INC.	Europe	MIMAKI EUROPE B.V.
Brazil	MIMAKI BRASIL COMERCIO E IMPORTACAO LTDA	Indonesia	PT. MIMAKI INDONESIA
India	MIMAKI INDIA PRIVATE LIMITED	Australia	MIMAKI AUSTRALIA PTY. LTD.
Taiwan	MIMAKI ENGINEERING (TAIWAN) CO.,LTD.	China	SHANGHAI MIMAKI TRADING CO.,LTD.
Singapore	MIMAKI SINGAPORE PTE. LTD.	Thailand	MIMAKI (THAILAND) CO.,LTD.
Vietnam	MIMAKI VIETNAM CO., LTD.		

DB30363-01

Mimaki

DTF (Direct To Film) Printer

TXF330-800

Keep Printing.
Keep Creating.



C M Y K + W

Productivity-Focused Operation Style

[High productivity with reliable quality]

Two styles to choose from,
tailored to your workflow.

C M Y K SB PP + W

Creativity-Focused Operation Style

[Vivid color output enabled by 6-color inks]

Even at 1.5 × productivity, achieve dense, beautiful solids and smooth gradations.

*Compared to previous models

The addition of Sky Blue & Pale Pink delivers even more vibrant color output.



Production mode
11.5 sqm/h

Outstanding image quality powered by the flagship 330 Engine



Uniform, beautiful solid fills
High-density printheads deliver excellent image quality even at high speeds



Smooth gradations with reduced graininess
Precise control of droplets as small as 4 pl

Mass production of large-format graphic T-shirts at approx. 90 pieces/hour*




Large T-shirts 94 pcs/h
Production mode 600×1200 6P 11.5 sqm/h



Large T-shirts 62 pcs/h
Production mode 720×720 6P 7.5 sqm/h

Print condition: H300 mm x W400 mm graphics are arranged on a full-size DTF film and printed.
*Varies depending on design margins and print settings. Values are not guaranteed.

A wide range of print modes to match your design needs



Draft

Light-color or white-only designs



High Speed 1

High-density output with high-speed printing



Expand your business through creative versatility

Smooth skin tones without graininess

Even skin tones prone to graininess and delicate hair gradations are rendered smoothly, delivering beautiful and accurate results for applications that demand high reproducibility.




Take design quality to the next level

From logos to intricate details, target colors are reproduced with precision delivering a finish that instantly communicates your brand identity.



Minimized Operator Workload with Stable Operation During Long Print Runs.



Non-stop printing on 100 m roll DTF film

- Supports up to 4 L of white ink
- Continuous operation without interruption, even for long overnight jobs



Replace ink without stopping production

- Auto-switches to another cartridge when ink runs out
- Empty cartridges can be replaced during printing




Enhanced reliability for high-speed and long-run printing with a new media transport system

- The newly developed MFT* ensures high-precision quality, even during extended long-run printing


*Mimaki Feed Tension Technology

Stable and Reliable Production Powered by Mimaki Core Technologies.



MCT Version2 (Mimaki Circulation Technology 2)

Full ink circulation system stabilizes white ink discharge. Reduces ink waste during nozzle cleaning for more efficient operation.



NCU (Nozzle Check Unit)

A sensor detects missing nozzles and automatically performs cleaning, preventing defective output and reducing material waste.

NRS (Nozzle Recovery System)

If a nozzle cannot be recovered, printing continues using substitute nozzles—ensuring uninterrupted production.

*The function may be limited by missing-nozzle position and amount