

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Safety Data Sheets

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name CS100 Black Product Description CS100-K-BB Product Use INK JET ink Restrictions on Use None known.

Manufacturer Information

Mimaki Engineering Co., Ltd 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 Japan Phone: +81-268-64-2413

Importer / Distributor Information

MIMAKI AUSTRALIA PTY LTD. Unit 14, 38-46 South Street, Rydalmere, NSW 2116, Australia Phone: + 61-2-8036-4500

Emergency telephone number

+61 2 8014 4558 (within Australia only) 18000 74234 (within Australia only) +65 3158 1074

Section 2 - HAZARDS IDENTIFICATION

Classified to Globally Harmonised System of Classification and Labelling of Chemicals, Third revised edition, published by the United Nations as modified under Schedule 6 of the Work Health and Safety Regulation. **GHS** Classification Flammable Liquids - Category 4 Acute Toxicity - Inhalation - Vapor - Category 4 (27% unknown) Serious Eye Damage/Eye Irritation - Category 1 Carcinogenicity - Category 2 Reproductive Toxicity - Category 1B Specific Target Organ Toxicity - Single Exposure - Category 1 (Central Nervous System, Hematopoietic System, kidneys) Specific Target Organ Toxicity - Single Exposure - Category 2 (blood) Specific Target Organ Toxicity - Single Exposure - Category 3 Specific Target Organ Toxicity - Repeated Exposure - Category 2 (Hematopoietic System, kidneys, respiratory system) Hazardous to the Aquatic Environment - Chronic - Category 3 **GHS Label Elements** Symbol(s)



MIMCIKI Safety Data Sheets

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Signal Word Danger Hazard Statement(s) Combustible liquid. Harmful if inhaled. Causes serious eye damage. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. **Precautionary Statement(s)** Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Use Personal Protective equipment as required. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Response In case of fire: Use appropriate media for extinction. If exposed: Call a POISON CENTER or doctor/physician. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Storage Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Disposal Dispose of contents/container in accordance with local/regional/national/international regulations. Statement(s) of Unknown Acute Toxicity Inhalation 27% of the mixture consists of ingredient(s) of unknown acute toxicity. **Potential Environmental Effects** Harmful to aquatic life with long lasting effects. Other Hazards Which Do Not Result in Classification None known. Main Symptoms and Emergency Overview Harmful if inhaled. Causes serious eye damage. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Mimciki[®] Safety Data Sheets

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

CAS	CAS Component Name						
112-07-2	Ethylene glycol monobutyl ether acetate	50-60					
108-65-6	Propylene glycol monomethyl ether acetate	15-25					
96-48-0	.gammaButyrolactone	15-25					
1333-86-4	Carbon black	1-5					
Trade Secret	Vinyl chloride-vinyl acetate copolymers	1-10					
Trade Secret	Additives	0.1-5					

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. Skin

Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Symptoms: Immediate

Harmful if inhaled, eye damage, central nervous system damage, kidney damage, hematopoietic effects, blood damage, respiratory tract irritation, central nervous system depression

Symptoms: Delayed

Cancer, reproductive effects, hematopoietic effects, kidney damage, respiratory system damage Indication of any immediate medical attention and special treatment needed Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Water spray, carbon dioxide, regular dry chemical, alcohol resistant foam

Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

Special Hazards Arising from the Chemical

Combustible liquid and vapor

Hazardous Combustion Products

Oxides of carbon

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

∕∕IIMCIKI[™]

Safety Data Sheets

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. **Hazchem/Emergency Action Code**

2Z

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray. Small spills. Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills. Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not breathe vapor or mist. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Wear protective gloves/clothing and eye/face protection. Do not eat, drink, or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

Store and handle in accordance with all current regulations and standards. Grounding and bonding required. Keep separated from incompatible substances.

Incompatible Materials

Acids, bases, oxidizing materials, halogens, amines

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Ethylene glycol monobutyl ether acetate	112-07-2			
Safe Work Australia.	20 ppm TWA ; 133 mg/m3 TWA			
	50 ppm STEL ; 333 mg/m3 STEL			
ACGIH:	20 ppm TWA			

Mimaki

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Safety Data Sheets

Propylene glycol monomethyl ether acetate	108-65-6
Safe Work Australia.	50 ppm TWA ; 274 mg/m3 TWA
	100 ppm STEL ; 548 mg/m3 STEL
Carbon black	1333-86-4
Safe Work Australia.	3 mg/m3 TWA
ACGIH:	3 mg/m3 TWA inhalable particulate matter

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

Consult with a health and safety professional for specific respirators appropriate for your use.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	black liquid	Physical State	liquid		
Odor	solvent odor	Color	black		
Odor Threshold	Not available	рН	Not available		
Melting Point	<-30 °C	Boiling Point	Not available		
Boiling Point Range	145-209 °C	Freezing point	Not available		
Evaporation Rate	Not available	Flammability (solid, gas)	Not applicable		
Autoignition Temperature	Not available	Flash Point	65 ±1 °C		
Lower Explosive Limit	Not available	Decomposition temperature	Not available		
Upper Explosive Limit Not available		Vapor Pressure	0.493 kPa (20 °C)		
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.995 ± 0.01		



			(25 °C)
Water Solubility	(slightly soluble)	Partition coefficient: n- octanol/water	Not available
Viscosity	3.7 - 4.3 mPa·s (25 °C)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form liquid		Molecular Weight	Not available

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected. Chemical Stability Stable under normal conditions of use. Possibility of Hazardous Reactions Will not polymerize. Conditions to Avoid Avoid flames, sparks, and other sources of ignition. Containers may rupture or explode if exposed to heat. Avoid contact with incompatible materials. Incompatible Materials Acids, bases, oxidizing materials, halogens, amines Hazardous decomposition products

Oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure Inhalation irritation, difficulty breathing, vomiting, unconsciousness, loss of coordination, headache, drowsiness, dizziness, nausea, cancer, reproductive effects, blood effects **Skin Contact** mild irritation **Eve Contact** irritation Ingestion irritation, nausea, vomiting, headache, drowsiness, dizziness, stomach pain Acute and Chronic Toxicity **Component Analysis - LD50/LC50** The components of this material have been reviewed in various sources and the following selected endpoints are published: Ethylene glycol monobutyl ether acetate (112-07-2) Oral LD50 Rat 2400 mg/kg Dermal LD50 Rabbit 1500 mg/kg Inhalation LC50 Rat >400 ppm 4 h Propylene glycol monomethyl ether acetate (108-65-6)



Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Safety Data Sheets

Oral LD50 Rat 8532 mg/kg Dermal LD50 Rabbit >5 g/kg .gamma.-Butyrolactone (96-48-0) Oral LD50 Rat 1540 mg/kg Inhalation LC50 Rat >5100 mg/m3 4 h (no deaths occurred) Carbon black (1333-86-4) Oral LD50 Rat >15400 mg/kg Product Toxicity Data Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Immediate Effects

Harmful if inhaled, eye damage, central nervous system damage, kidney damage, hematopoietic effects, blood damage, respiratory tract irritation, central nervous system depression

Delayed Effects

Cancer, reproductive effects, hematopoietic effects, kidney damage, respiratory system damage

Irritation/Corrosivity Data

eye damage, respiratory tract irritation

Respiratory Sensitization No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Ethylene glycol monobutyl ether acetate	112-07-2
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
DFG:	Category 4 (no significant contribution to human cancer)
.gammaButyrolactone	96-48-0
IARC:	Monograph 71 [1999] ; Supplement 7 [1987] ; Monograph 11 [1976] (Group 3 (not classifiable))
Carbon black	1333-86-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010] ; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man ;inhalable fraction)
OSHA:	Present
NIOSH:	potential occupational carcinogen



Vinyl chloride-vinyl acetate copolymers	Trade Secret
IARC:	Supplement 7 [1987] ; Monograph 19 [1979] (Group 3 (not classifiable))
Germ Cell Mutagenicity No information available for the prod Reproductive Toxicity Available data characterizes component	uct.

Available data characterizes components of this product as reproductive hazards. Specific Target Organ Toxicity - Single Exposure blood, central nervous system, kidneys, hematopoietic system, respiratory tract. Specific Target Organ Toxicity - Repeated Exposure Hematopoietic System, kidneys, respiratory system Aspiration hazard No information available for the product. Medical Conditions Aggravated by Exposure respiratory disorders

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Analysis - Aquatic To	8
Ethylene glycol monobutyl ether acetate	112-07-2
Algae:	EC50 72 h Desmodesmus subspicatus >500 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 37 mg/L IUCLID
Propylene glycol monomethyl ether acetate	108-65-6
Fish:	LC50 96 h Pimephales promelas 161 mg/L [static]
Invertebrate:	EC50 48 h Daphnia magna >500 mg/L IUCLID
.gammaButyrolactone	96-48-0
Algae:	EC50 72 h Desmodesmus subspicatus 360 mg/L IUCLID ; EC50 96 h Desmodesmus subspicatus 79 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna Straus >500 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility in soil

No information available for the product.

Other adverse effects



No data available

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations.

Section 14 - TRANSPORT INFORMATION

ADG Information:

No Classification assigned.

IATA Information:

No Classification assigned.

ICAO Information:

No Classification assigned.

IMDG Information:

No Classification assigned.

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Ethylene glycol monobutyl ether acetate	112-07-2
IBC Code:	Category Y
Propylene glycol monomethyl ether acetate	108-65-6
IBC Code:	Category Z
.gammaButyrolactone	96-48-0
IBC Code:	Category Y

Transportation Special Precautions

No information available for the product.

Hazchem/Emergency Action Code

2Z

Section 15 - REGULATORY INFORMATION

Australia Regulations

Work Health and Safety Regulations - Prohibited Carcinogens
No component(s) are listed on the Prohibited Carcinogens list.
Work Health and Safety Regulations - Restricted Carcinogens
No component(s) are listed on the Restricted Carcinogens list.

Work Health and Safety Regulations - Restricted Hazardous Chemicals

No component(s) are listed on the Restricted Hazardous Chemicals list

Australia Work Health and Safety Regulations - Hazardous Chemicals Requiring Health Monitoring None of this product's components are on the list.

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25



Safety Data Sheets

Component Analysis - Inventory

Ethylene glycol monobutyl ether acetate (112-07-2)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Propylene glycol monomethyl ether acetate (108-65-6)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

.gamma.-Butyrolactone (96-48-0)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Carbon black (1333-86-4)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Vinyl chloride-vinyl acetate copolymers (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes

Additives (Trade Secret)

US	CA	EU	AU	РН		JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
No	No	No	No	No	No	No	No						



Safety Data Sheets

Product Name: CS100 Black SDS No. 037-S153414 First issue: 2017/10/20 Revised: 2024/06/25

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG -Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN -European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL -Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ -ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL -Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA -Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS -Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

The information set forth in this Safety Data Sheet does not purport to be all-inclusive and should be used only as a guide. While the information and recommendations set forth herein are believed to be accurate, the company makes no warranty regarding such information and recommendations and disclaims all liability from reliance thereon.