

Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

AS5 ink Black

Product Description

AS5-K-60 / AS5-K-2L

Product Use

INK JET Ink

Restrictions on Use

None known.

Manufacturer Information

Mimaki Engineering Co., Ltd Telephone number: +81-268-64-2413

2182-3 Shigeno-otsu, Tomi-shi, Nagano

389-0512 Japan

Importer / Distributor Information

MIMAKI AUSTRALIA PTY LTD. Telephone number: + 61-2-8036-4500

Unit 14, 38-46 South Street, Rydalmere, NSW 2116, Australia

Emergency telephone number

+61 2 8014 4558 (within Australia only) 18000 74234 (within Australia only)

+65 3158 1074

Section 2 - HAZARDS IDENTIFICATION

Classified to Globally Harmonised System of Classification and Labelling of Chemicals, Third revised edition, published by the United Nations as modified under Schedule 6 of the Work Health and Safety Regulation.

GHS Classification

Flammable Liquids - Category 4

Serious Eye Damage/Eye Irritation - Category 2A

Carcinogenicity - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 2 (Central Nervous System)

Specific Target Organ Toxicity - Repeated Exposure - Category 1 (lungs)

GHS Label Elements

Symbol(s)





Signal Word

Danger

Hazard Statement(s)

Combustible liquid.

Causes serious eye irritation.

Suspected of causing cancer.



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

May cause damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Use Personal Protective equipment as required.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response

In case of fire: Use appropriate media for extinction.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards Which Do Not Result in Classification

None known.

Main Symptoms and Emergency Overview

Black liquid. Combustible liquid. Causes serious eye irritation. Suspected of causing cancer. May cause damage to organs.

Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
Trade Secret	Glycol ether solvents	70-80
96-48-0	.gammaButyrolactone	10-20
1333-86-4	Carbon black	1-10
Trade Secret	Chlorinated Ethylene-Vinyl Acetate Copolymer (CEVA)	1-10
Trade Secret	Acrylic type resin	1-10
Trade Secret	Additive	0.1-5

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Give artificial respiration if not breathing. Call a POISON CENTER or doctor/physician.

Skii

Gently wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash before re-use.

Eyes



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation or pain persists after fifteen minutes of eye irrigation, seek medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Symptoms: Immediate

eye irritation, central nervous system damage

Symptoms: Delayed cancer, lung damage

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

carbon dioxide, regular dry powder, regular dry chemical, water spray, alcohol resistant foam

Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

Special Hazards Arising from the Chemical

Combustible liquid and vapor. Irritating fumes and gases may be released upon thermal processing or during combustion.

Hazardous Combustion Products

oxides of carbon, oxides of nitrogen

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

Hazchem/Emergency Action Code

No data available

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray. Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Obtain special instructions before use. Do not handle

Page 3 of 8

Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

Safety Data Sheets

until all safety precautions have been read and understood. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke when using this product. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep cool.

Store locked up.

Store and handle in accordance with all current regulations and standards. Keep container tightly closed. Grounding and bonding required. Keep separated from incompatible substances.

Incompatible Materials

acids, bases, oxidizing materials, halogens

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

	1
Carbon black	1333-86-4
Australia:	3 mg/m3 TWA
ACGIH:	3 mg/m3 TWA inhalable fraction

EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

Consult with a health and safety professional for specific respirators appropriate for your use.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	black liquid	Physical State	liquid
Odor	solvent odor	Color	black
Odor Threshold	Not available	pН	Not available
Melting Point	Not available	Boiling Point	Not available
Freezing point	Not available	Evaporation Rate	Not available
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	169 °C (Glycol ether type	Flash Point	70 °C (158 °F)
	solvent)		
Lower Explosive	2.5 vol% (Glycol ether type	Decomposition temperature	Not available
Limit	solvent)		
Upper Explosive	33 vol% (Glycol ether type	Vapor Pressure	<=0.1 kPa at 20 °C (Glycol ether
Limit	solvent)		type solvent)
Vapor Density	Not available	Specific Gravity (water=1)	Not available
(air=1)			
Water Solubility	Not available	Partition coefficient: n-	Not available



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

		octanol/water	
Viscosity	4 - 4.5 mPa-s 25 °C	Solubility (Other)	Not available
Density	0.969 g/cm3	Physical Form	liquid
Molecular Weight	Not available		

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks, and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

acids, bases, oxidizing materials, halogens

Hazardous decomposition products

oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

irritation, headache, cancer, dizziness, drowsiness, lung damage

Skin Contact

irritation, skin disorders

Eye Contact

irritation

Ingestion

vomiting, nausea

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Glycol ether solvents (Trade Secret)

Oral LD50 Rat 6500 µL/kg

.gamma.-Butyrolactone (96-48-0)

Oral LD50 Rat 1540 mg/kg

Inhalation LC50 Rat >5100 mg/m3 4 h (no deaths occurred)

Carbon black (1333-86-4)

Oral LD50 Rat >15400 mg/kg

Additive 2 (Trade Secret)

Oral LD50 Rat 40 g/kg

Dermal LD50 Rabbit >20 mL/kg (no deaths occurred)

Immediate Effects

eye irritation, central nervous system damage

Delayed Effects

lung damage, cancer

Irritation/Corrosivity Data

eye irritation



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Component Caremogementy	
.gammaButyrolactone	96-48-0
IARC:	Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 3
	(not classifiable))
Carbon black	1333-86-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly
	carcinogenic to humans))
DFG:	Category 3B (could be carcinogenic for man, inhalable fraction)
OSHA:	Present
NIOSH:	potential occupational carcinogen
Chlorinated Ethylene-Vinyl Acetate Copolymer	Trade Secret
(CEVA)	
IARC:	Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

Germ Cell Mutagenicity

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

central nervous system

Specific Target Organ Toxicity - Repeated Exposure

lungs

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

No information available for the product.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Component Imarysis	i i i i i i i i i i i i i i i i i i i
.gamma	96-48-0
Butyrolactone	
Algae:	EC50 72 h Desmodesmus subspicatus 360 mg/L IUCLID; EC50 96 h Desmodesmus subspicatus 79
	mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna Straus >500 mg/L IUCLID
Additive	Trade Secret
Algae:	EC50 72 h Desmodesmus subspicatus 8 mg/L IUCLID

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility in soil

No information available for the product.

Other adverse effects

No additional information is available.

Page 6 of 8



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Empty containers may contain product residue.

Section 14 - TRANSPORT INFORMATION

ADG Information:

No Classification assigned.

IATA Information:

No Classification assigned.

ICAO Information:

No Classification assigned.

IMDG Information:

No Classification assigned.

Component Marine Pollutants (IMDG)

Not regulated as dangerous goods.

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

.gammaButyrolactone	96-48-0
IBC Code:	Category Y

Transportation Special Precautions

No information available for product.

Hazchem/Emergency Action Code

No data available

Section 15 - REGULATORY INFORMATION

Australia Regulations

Work Health and Safety Regulations - Prohibited Carcinogens

No component(s) are listed on the Prohibited Carcinogens list.

Work Health and Safety Regulations - Restricted Carcinogens

No component(s) are listed on the Restricted Carcinogens list.

Work Health and Safety Regulations - Restricted Hazardous Chemicals

No component(s) are listed on the Restricted Hazardous Chemicals list:

Work Health and Safety Regulations - Hazardous Substances Requiring Health Monitoring

Component Analysis - Inventory

Glycol ether solvents (**Trade Secret**)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	NSL	EIN	Yes	No	Yes	No	No	No	Yes	Yes	No	Yes

.gamma.-Butyrolactone (96-48-0)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

Carbon black (1333-86-4)



Product Name: AS5 ink Black SDS No. 037-S285694 First issue: 2020/10/14

Revised:

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

Chlorinated Ethylene-Vinyl Acetate Copolymer (CEVA) (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

Additive (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD -Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR -Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory, EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law, JP - Japan; Kow - Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory, KECL - Korea Existing Chemicals List, KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI -List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL -Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA -Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act, TDG -Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information set forth in this Safety Data Sheet does not purport to be all-inclusive and should be used only as a guide. While the information and recommendations set forth herein are believed to be accurate, the company makes no warranty regarding such information and recommendations and disclaims all liability from reliance thereon.