

SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

1. Identification

Product Name : LUS-120 Light Magenta

Order No. : LUS12-LM-BA / LUS12-LM-B2

Ink Ver. : 1

General Use : Ink jet printing ink

Product Description : UV Inkjet ink

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413 Importer / Distributor Established in Australia

: MIMAKI AUSTRALIA PTY LTD. Company Name

Address : Unit 14, 38-46 South Street, Rydalmere, NSW 2116, Australia

: +61-2-8036-4500 Telephone No.

Emergency Telephone No. : +61 2 8014 4558 (within Australia only)

18000 74234 (within Australia only)

+65 3158 1074

Hazards Identification

Classified as a hazardous product in accordance with the criteria of Safe Work Australia

Globally Harmonized System (GHS)

Classified as dangerous goods in accordance with the Australian Code for the Transport of

Dangerous Goods by Road and Rail (ADG)

[GHS Classification]

Acute Toxicity - Oral : Category 4 Skin Corrosion / Irritation : Category 2 Eve Damage / Irritation : Category 1 Sensitization – Skin : Category 1A Toxic to Reproduction : Category 1B Specific Target Organ Toxicity : Category 1

(Repeated Exposure)

Hazardous to the Aquatic : Category 2

Environment - Acute Hazard

Hazardous to the Aquatic : Category 2

Environment - Long Term Hazard



SDS No. 037-U112010 First issue: 2017/04/07 Revised: 2024/06/27

Safety Data Sheets

The above list does not include category being non-classifiable or not-applicable.

[Label Elements]

Symbol



Signal Word Danger

Hazard Statements

H302 Harmful if swallowed.

H315 Causes skin irritation

H318 Cause serious eye damage

H317 May cause an allergic skin reaction

H360 May damage fertility or the unborn child

H372 Causes damage to organs through prolonged or repeated exposure(Liver, respiratory tract)

H411 Toxic to aquatic life with long lasting effects

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's Operation Manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe gas/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P273 Avoid release to the environment.

[Response]

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

(P301)+P330 (IF SWALLOWED): Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(P305)+P310 (IF IN EYES): Immediately call a POISON CENTER or doctor/physician.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

[Storage]

P405 Store locked up.

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).



Safety Data Sheets

Product Name: LUS-120 Light Magenta SDS No. 037-U112010

> First issue: 2017/04/07 Revised: 2024/06/27

[Other hazards]

Not Applicable.

3. Composition / Information on Ingredients

Substance/mixture: mixture

| Chemical Name | CAS No | weight-% |
|--|-------------|----------|
| 2-Propenoic acid, 2-phenoxyethyl ester | 48145-04-6 | 20-30 |
| 2-Propenoic acid, (tetrahydro-2-furanyl)methyl ester | 2399-48-6 | 20-30 |
| 2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo- | 5888-33-5 | 10-20 |
| 2H-Azepin-2-one, 1-ethenylhexahydro- | 2235-00-9 | 10-20 |
| Acrylate monomer | CBI | 5-15 |
| Diphenyl-2,4,6-trimethylbenzoyl phosphine oxide | 75980-60-8 | 1-5 |
| Additives | CBI | <1 |
| Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)- | 162881-26-7 | <1 |
| Colorant | CBI | <1 |
| Photoinitiator | CBI | <1 |
| Others | CBI | <1 |

4. First Aid Measures

[Description of first aid measures]

General advice : Show this safety data sheet to the doctor in attendance. Do not delay

care and transport of a seriously injured person. IF exposed or

concerned: Get medical advice/attention.

Inhalation : Move victim to fresh air. Get medical attention.

Skin Contact : Wash off immediately with soap and plenty of water while removing

all contaminated clothes and shoes. Get immediate medical

advice/attention.

Eye Contact : IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Get immediate medical advice/attention.

Immediately call a POISON CENTER or doctor/physician.

Ingestion : Rinse mouth thoroughly with water. Never give anything by mouth

to an unconscious person. If vomiting occurs spontaneously, keep

head below hips to prevent aspiration. Get medical attention.

Self-protection of the first : Wear personal protective clothing (see section 8). Do not use

aider mouth-to-mouth method if victim ingested or inhaled the substance;



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

[Symptoms caused by exposure]

Symptoms : Prolonged contact may cause redness and irritation. May cause

> blindness. Coughing and/ or wheezing. Hives. Itching. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Rashes.

[Medical attention and specialtreatment]

Note to physicians : May cause sensitization of susceptible persons.

5. Fire Fighting Measures

: Flash Pont、95 $^{\circ}$ C / 203 $^{\circ}$ F Flammable Properties

Suitable Extinguishing : Use CO2, dry chemical, or foam, Use extinguishing measures that

Media are appropriate to local circumstances and the surrounding

environment

Unsuitable Extinguishing DDo not use a solid water stream as it may scatter and spread fire.

Media

Specific hazards arising : Risk of ignition. The product causes irritation of eyes, skin and

from the chemical mucous membranes. Thermal decomposition can lead to release of

> irritating and toxic gases and vapors. Product is or contains a sensitizer. The product causes burns of eyes, skin and mucous

membranes.

: Firefighters should wear self-contained breathing apparatus and Special protective

full firefighting turnout gear. Use personal protection equipment. equipment and

precautions for fire

fighters

6. Accidental Release Measures

[Personal Precautions, Protective Equipment and Emergency Procedures]

Personal precautions : Evacuate personnel to safe areas. Ensure adequate ventilation,

> especially in confined areas. Keep people away from and upwind of spill/leak. Use personal protection recommended in Section 8. Avoid

contact with skin, eyes or clothing.

For emergency : Use personal protection recommended in Section 8.

responders



SDS No. 037-U112010 First issue: 2017/04/07 Revised: 2024/06/27

Safety Data Sheets

Environmental : Prevent entry into waterways, sewers, basements or confined areas.

Precautions

[Methods and material for containment and cleaning up]

Methods for containment : Prevent further leakage or spillage if safe to do so. Cover with

plastic sheet to prevent spreading. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up : Use personal protective equipment as required. Clean contaminated

surface thoroughly. Pick up and transfer to properly labeled

containers. Take up with sand or other non-combustible absorbent

material and place into containers for later disposal.

Reference to other

sections

: See Section 12: ECOLOGICAL INFORMATION.

7. Handling and Storage

[Precautions for Safe Handling]

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice. Use personal protective equipment as required. Ensure

adequate ventilation, especially in confined areas. Do not eat, drink or

smoke when using this product.

General Hygiene : Regular cleaning of equipment, work area and clothing is

Considerations recommended. Do not eat, drink or smoke when using this product.

Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before reuse.

Contaminated work clothing should not be allowed out of the workplace. Avoid breathing dust/fume/gas/mist/vapors/spray.

[Conditions for Safe Storage, including any Incompatibilities]

Storage Conditions : Keep away from heat. Keep container tightly closed. Keep in properly

labeled containers. Store locked up.

[Specific end use(s)]

Risk Management : The information required is contained in this Safety Data Sheet.

Methods (RMM)

8. Exposure Controls / Personal Protection

[Control parameters]

Exposure Limits



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

| Chemical Name | Australia | ACGIH |
|---------------|-----------|---------------------------------|
| Caprolactam | 10 mg/m3 | TWA: 5 mg/m3 inhalable fraction |
| 105-60-2 | 1 mg/m3 | and vapor |

Caprolactam is non-intentionally added substance, contains less than 1% in the product

[Appropriate engineering controls]

: Showers. **Engineering Controls**

> Eyewash stations. Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection : Face protection shield. Tight sealing safety goggles.

Hand Protection : Impervious gloves.

Skin and body : Rubber boots. Long sleeved clothing. Impervious clothing. Chemical

protection resistant apron. Respiratory : Vapor mask.

protection

Environmental Do not allow into any sewer, on the ground or into any body of water.

exposure controls

Physical and Chemical Properties

- Physical State : liquid Appearance

> - Color : red

Odor : Characteristic odor Odor Threshold : No data available pН : No data available Melting point/freezing point : No data available Boiling point/boiling range : No data available

: 95 °C / 203 °F (Acceptance by the lowest flash point) Flash point

: No data available Evaporation rate : No data available Flammability (solid, gas) Flammability Limits in Air : No data available

Upper flammability limits

Lower flammability limit

Vapor Pressure : No data available Vapor density : No data available



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

: 1.0-1.1 Specific gravity

Solubility(ies) : Immiscible in water Partition coefficient : No data available : No data available Autoignition temperature Decomposition temperature : No data available : No data available Kinematic viscosity Dynamic viscosity $: 7-12 \text{ mPa} \cdot \text{s}(25 \text{ deg.C})$

[Other information]

Molecular weight : No data available : No data available Explosive properties Oxidizing properties : No data available Softening point : No data available VOC Content (%) : No data available Density : No data available Bulk density : No data available

10. Stability and Reactivity

: No information available. Reactivity

Chemical Stability : Stable under the normal storage and use. Explosion data : Sensitivity to Mechanical Impact; None.

Sensitivity to Static Discharge; Yes.

Possibility of Hazardous : No information available.

Reactions

Hazardous : None under normal processing.

polymerization

Conditions to Avoid : Heat, flames and sparks.

Incompatible Materials : Strong oxidizing agents. Finely powdered metals.

Hazardous : None known based on information supplied.

decomposition products

11. Toxicological Information

[Information on likely routes of exposure]

Acute Toxicity

Inhalation : Irritating to respiratory system.

Eye contact : Irritating to eyes. Causes serious eye damage. May cause irreversible



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

damage to eyes.

Skin Contact : Harmful in contact with skin. Causes skin irritation. Repeated or

prolonged skin contact may cause allergic reactions with susceptible

persons.

Ingestion : Harmful if swallowed. Ingestion may cause irritation to mucous

membranes. May be harmful if swallowed and enters airways.

Symptoms : Coughing and/ or wheezing. May cause redness and tearing of the

eyes. Redness. Burning. May cause blindness. Hives. Itching. May

cause allergic skin reaction. Rashes.

Unknown Acute Toxicity

1.6 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

27.4 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

The following values are calculated based on chapter 3.1 of the GHS document

| Chemical Name | Oral LD50 | Dermal LD50 |
|---------------|----------------------|----------------------|
| Product | ATEmix = 1882.3mg/kg | ATEmix = 2220.9mg/kg |

Acute toxicity In calculating the ATE for product classification, the converted acute toxicity value estimate is used.

[Delayed and immediate effects as well as chronic effects from short and long-term exposure]

Skin corrosion : Based on available data, the classification criteria are not met.

In Vitro Acute Dermal Corrosivity Study Episkin test□GLP OECD

TG431

In this in vitro EPISKIN model test with similar product, the result

indicates that the product is non-corrosive to the skin.

Skin irritation : Classification is based on mixture calculation methods based on

component data. Irritating to skin.

Serious eye damage/eye :

: Classification is based on mixture calculation methods based on

irritation component data. Risk of

component data. Risk of serious damage to eyes.

Respiratory or skin : Classification is based on mixture calculation methods based on

sensitization component data. May cause sensitization by skin contact. May cause

sensitization in susceptible persons.

Germ cell mutagenicity : Classification is based on mixture calculation methods based on

component data. Based on available data, the classification criteria are

not met.

Carcinogenicity : Classification is based on mixture calculation methods based on



SDS No. 037-U112010 First issue: 2017/04/07 Revised: 2024/06/27

Safety Data Sheets

component data Based on available data, the classification criteria are

not met.

Reproductive toxicity : Classification is based on mixture calculation methods based on

component data. Contains material that may cause adverse

reproductive effects.

STOT - single exposure : Classification is based on mixture calculation methods based on

component data. Based on available data, the classification criteria are

not met.

STOT - repeated : Classification is based on mixture calculation methods based on

exposure component data. Causes damage to organs through prolonged or

repeated exposure.

Aspiration hazard : Classification is based on mixture calculation methods based on

component data. Based on available data, the classification criteria are

not met.

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it.

Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

Ecotoxicity

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|---------------|------------------------------|----------------------------|------------------------|
| Caprolactam | EC50 (72h): = 130 mg/L | LC50 (96h, static): = 930 | EC50 (48h): 828 - 2920 |
| | (Desmodesmus subspicatus) | mg/L (Lepomis macrochirus) | mg/L (Daphnia magna) |
| | EC50 (96h): = 160 mg/L | LC50 (96h, static): = 1400 | EC50 (48h): > 500 mg/L |
| | (Desmodesmus subspicatus) | mg/L (Pimephales promelas) | (Daphnia magna Straus) |
| | EC50 (72h): 4320 – 4800 mg/L | | |
| | (Pseudokirchneriella) | | |

Caprolactam is non-intentionally added substance, contains less than 1% in the product

Persistence and : No data available.

Degradability

Bioaccumulative : No data available.

potential

Mobility in soil : No data available.

Other adverse effects : No data available.



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

13. Disposal Considerations

[Waste treatment methods]

Waste from Residues / Disposal should be in accordance with applicable regional, national

Unused Products and local laws and regulations.

Contaminated : Disposal should be in accordance with applicable regional, national

and local laws and regulations. Improper disposal or reuse of this packaging

container may be dangerous and illegal.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

[ADG]

UN/ID no : UN3082

Environmentally hazardous substance, liquid, n.o.s. (2-Propenoic Proper shipping name

acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-, 2-Propenoic

acid, 2-phenoxyethyl ester)

Hazard Class : 9 : 111 **Packing Group** Environmental hazard : Yes

Special Provisions : 274, 331, 335, 375, AU01

: UN3082, Environmentally hazardous substance, liquid, n.o.s. Description

(2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-,

2-Propenoic acid, 2-phenoxyethyl ester), 9, III

[IMDG]

UN/ID no : UN3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s. (2-Propenoic

acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-, 2-Propenoic

acid, 2-phenoxyethyl ester)

Hazard Class : 9 **Packing Group** : 111

Marine pollutant : This material meets the definition of a marine pollutant

Environmental hazard

Special Provisions : 2.10.2.7 *1 EmS-No : F-A, S-F

Description : UN3082, Environmentally hazardous substance, liquid, n.o.s.



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

(2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-,

2-Propenoic acid, 2-phenoxyethyl ester), 9, III

[IATA]

UN/ID no : UN3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (2-Propenoic

acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-, 2-Propenoic

acid, 2-phenoxyethyl ester)

Hazard Class : 9
Packing Group : III
Environmental hazard : Yes

Special Provisions : A197 *1

ERG Code : 9L

Description : UN3082, Environmentally hazardous substance, liquid, n.o.s.

(2-Propenoic acid, 1,7,7-trimethylbicyclo[2.2.1]hept-2-yl ester, exo-,

2-Propenoic acid, 2-phenoxyethyl ester), 9, III

15. Regulatory Information

[Safety, health and environmental regulations/legislation specific for the substance or mixture] See section 8 for national exposure control parameters

Major hazard : Not applicable

(accident/incident

planning) regulation

National pollutant : Not applicable

inventory (Subject to reporting requirement)

BANNED and/or : This product does not contain substances subject to prohibition,

restricted authorization or restriction.

International : AICS-Australia-Australian Inventory of Chemical Substances.

Inventories Complies

16. Other Information

[Key or legend to abbreviations and acronyms used in the safety data sheet]

ACGIH (American Conference of Governmental Industrial Hygienists)

^{*1} Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is excepted from Dangerous Goods regulations — see UN Special Provision.



SDS No. 037-U112010 First issue: 2017/04/07

Revised: 2024/06/27

Safety Data Sheets

[Key literature references and sources for data]

No information available

[Reference]

LOLI Database (ChemADVISOR,Inc.)

Work Heaith and Safty(WHS) Regulation2011

[The reference on GHS classification results]

EU CLP(1272/2008)Annex VI Table 3

[Disclaimer]

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.