

Safety Data Sheets

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Dye Sublimation Ink Sb410 Black T

Product Description

SB410-KT-2L

Product Use

INK JET ink

Restrictions on Use

None known.

Manufacturer Information

Mimaki Engineering Co., Ltd
2182-3 Shigeno-otsu, Tomi-shi, Nagano
389-0512 Japan

Telephone number: +81-268-64-2413

Emergency telephone number: +81-268-64-2281

Importer / Distributor Information

MIMAKI AUSTRALIA PTY LTD.
Unit 14, 38-46 South Street, Rydalmere, NSW 2116, Australia

Telephone number: + 61-2-8036-4500

Section 2 - HAZARDS IDENTIFICATION

Classified to Globally Harmonised System of Classification and Labelling of Chemicals, Third revised edition, published by the United Nations as modified under Schedule 6 of the Work Health and Safety Regulation.

GHS Classification

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

GHS Label Elements**Symbol(s)****Signal Word**

Warning

Hazard Statement(s)

Causes skin irritation.

Causes serious eye irritation.

May cause allergic skin reaction.

Precautionary Statement(s)**Prevention**

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



Product Name: Dye Sublimation Ink Sb410 Black T

SDS No. 037-W381986

First issue: 2017/04/06

Revised:

Safety Data Sheets

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Potential Environmental Effects

None known.

Other Hazards Which Do Not Result in Classification

None known.

Main Symptoms and Emergency Overview

Causes skin irritation. Causes eye irritation. May cause allergic skin reaction.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
57-55-6	1,2-Propylene glycol	10-20
56-81-5	Glycerin	5-15
Trade Secret	Painting material	1-10
Trade Secret	Other	<10
Not Available	PROXEL XL2	0.2

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin

Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before re-use.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Symptoms: Immediate

May cause allergic skin reactions, skin irritation, eye irritation

Symptoms: Delayed

May cause allergic skin reactions

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

carbon dioxide, regular dry chemical, water spray, alcohol resistant foam

Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

Special Hazards Arising from the Chemical

Negligible fire hazard.



Safety Data Sheets

Hazardous Combustion Products

oxides of carbon, acrolein, oxides of sulfur

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products.

Hazchem/Emergency Action Code

No data available

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray. Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Avoid breathing dust, mist, fumes or vapors. Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke when using this product. Wear suitable protective gloves and eye/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Further information on storage conditions: Store and handle in accordance with all current regulations and standards. Store in a well-ventilated area. Keep container tightly closed. Keep cool. Keep separated from incompatible substances.

Incompatible Materials

acids, bases, oxidizing materials, metal oxides, peroxides, reducing agents, combustible materials, halocarbons, metals, metal salts

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

1,2-Propylene glycol	57-55-6
Safe Work Australia.	150 ppm TWA total vapour and particulates ; 474 mg/m3 TWA total vapour and particulates ; 10 mg/m3 TWA particulates only
Glycerin	56-81-5
Safe Work Australia.	10 mg/m3 TWA (containing no asbestos and <1% crystalline silica) inhalable dust, mist

EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment



Safety Data Sheets

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

Consult with a health and safety professional for specific respirators appropriate for your use.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	black liquid	Physical State	liquid
Odor	characteristic odor	Color	black
Odor Threshold	Not available	pH	7 - 9
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	(Not flammable)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1 - 1.2 (25 °C)
Water Solubility	(Easily soluble)	Partition coefficient: n-octanol/water	Not available
Viscosity	4 - 6 mPa-s (25 °C)	Solubility (Other)	Not available
Density	Not available	Physical Form	liquid
Molecular Weight	Not available		

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks, and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials

acids, bases, oxidizing materials, metal oxides, peroxides, reducing agents, combustible materials, halocarbons, metals, metal salts

Hazardous decomposition products

oxides of carbon, acrolein, oxides of sulfur

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure**Inhalation**

irritation

Skin Contact

irritation, allergic reactions

Eye Contact

irritation



Safety Data Sheets

Ingestion

irritation, nausea, vomiting, stomach pain

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

1,2-Propylene glycol (57-55-6)

Oral LD50 Rat 20 g/kg

Dermal LD50 Rabbit 20800 mg/kg

Glycerin (56-81-5)

Oral LD50 Rat 12600 mg/kg

Dermal LD50 Rabbit >10 g/kg

Inhalation LC50 Rat >570 mg/m3 1 h

Immediate Effects

May cause allergic skin reactions, skin irritation, eye irritation

Delayed Effects

May cause allergic skin reactions

Irritation/Corrosivity Data

skin irritation, eye irritation

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

May cause an allergic skin reaction.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

Not expected to be an aspiration hazard.

Medical Conditions Aggravated by Exposure

No information available for the product.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

1,2-Propylene glycol	57-55-6
Fish:	LC50 96 h Oncorhynchus mykiss 51600 mg/L [static]; LC50 96 h Oncorhynchus mykiss 41 - 47 mL/L [static]; LC50 96 h Pimephales promelas 51400 mg/L [static]; LC50 96 h Pimephales promelas 710 mg/L
Algae:	EC50 96 h Pseudokirchneriella subcapitata 19000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L [Static] EPA
Glycerin	56-81-5
Fish:	LC50 96 h Oncorhynchus mykiss 51 - 57 mL/L [static]

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility in soil



Product Name: Dye Sublimation Ink Sb410 Black T

SDS No. 037-W381986

First issue: 2017/04/06

Revised:

Safety Data Sheets

No information available for the product.

Other adverse effects

No additional information available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Empty containers may contain product residue.

Section 14 - TRANSPORT INFORMATION

ADG Information:

No Classification assigned.

IATA Information:

No Classification assigned.

ICAO Information:

No Classification assigned.

IMDG Information:

No Classification assigned.

Component Marine Pollutants (IMDG)

Not regulated as dangerous goods.

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

1,2-Propylene glycol	57-55-6
IBC Code:	Category Z

Transportation Special Precautions

No information available.

Hazchem/Emergency Action Code

No data available

Section 15 - REGULATORY INFORMATION

Australia Regulations

Work Health and Safety Regulations - Prohibited Carcinogens

No component(s) are listed on the Prohibited Carcinogens list.

Work Health and Safety Regulations - Restricted Carcinogens

No component(s) are listed on the Restricted Carcinogens list.

Work Health and Safety Regulations - Restricted Hazardous Chemicals

No component(s) are listed on the Restricted Hazardous Chemicals list:

Australia Work Health and Safety Regulations - Hazardous Chemicals Requiring Health Monitoring

None of this product's components are on the list.

Component Analysis - Inventory

1,2-Propylene glycol (57-55-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes

Glycerin (56-81-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes



Safety Data Sheets

Product Name: Dye Sublimation Ink Sb410 Black T

SDS No. 037-W381986

First issue: 2017/04/06

Revised:

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KECI - Korea Existing Chemicals Inventory; KECL - Korea Existing Chemicals List; KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

The information set forth in this Safety Data Sheet does not purport to be all-inclusive and should be used only as a guide. While the information and recommendations set forth herein are believed to be accurate, the company makes no warranty regarding such information and recommendations and disclaims all liability from reliance thereon.